




LED safety luminaire with optimised light distribution for the illumination of escape routes. Housing made of powder-coated aluminium for ceiling mounting with optional cable entry at the side. Incl. 4-chip LED illuminant for maximum safety.



Technical data

Material:	die-cast aluminum powder-coated	Apparent power:	4,4 VA
Illuminant:	1 x 1,8W LED-module	Effective power:	3,6 W
Luminous flux:	263 lm	Inrush current:	8 A / 50 µs
Nominal voltage AC:	230V ±10% 50/60 Hz	Protection class:	I
Nominal voltage DC:	176 - 264 V	Input terminals:	2.5mm ² feed through wiring
Nominal current AC:	19 mA	Temperature ta:	-15...+40 °C
Nominal current DC:	16 mA		




Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

	2.5	3.0	3.5	4.0	4.5	5.0	5.5	6.0	6.5	7.0
8.0	8.6	8.9	7.2	6.9	6.7	5.9	5.0	4.3	2.1	18.8
19.5	21.4	22.7	23.8	23.8	23.3	20.5	19.9	19.5	18.8	7.3
5.4	5.9	6.5	7.0	7.4	7.7	7.9	7.9	7.7	7.3	0.3
2.3	2.6	2.7	2.8	2.8	2.6	2.3	1.9	1.5	0.3	

Articles


SN 8400 -06 ALB LED J/SV round

Colors	RAL 9005	RAL 9016	RAL (special)
Art. no.	102058952	101301039	101301140
ceiling mounting	Light colour: 4000 K		Protection category: IP40




Chain suspension SN 8400 rd, RAL 9016

Art. no. 101445529




SN 8400 -06 ALB LED J/SV square

Colors	-	RAL 9005	RAL 9016
Art. no.	101301948	102059356	101301847
ceiling mounting	Light colour: 4000 K		Protection category: IP40



Cable suspension SN 8400 sq, RAL 9016

Art. no. 101445731



Name	Accessories	Art. no.
Chain suspension SN 8400 rd, RAL 9016	optional	101445529
Chain suspension SN 8400 sq, RAL 9016	optional	101445731