



Universal edge lights made of aluminium profile with frameless, free hanging acrylic legend panel.

Technical data


viewing distance:	22 m
Material:	aluminium
Illuminant:	12 x 0,1W LED-module
Nominal voltage AC:	230V ±10% 50/60 Hz
Nominal voltage DC:	176 - 264 V
Nominal current AC:	20 mA

Nominal current DC:	17 mA
Apparent power:	4,5 VA
Inrush current:	8 A / 50 µs
Protection class:	I
Input terminals:	2.5mm ² feed through wiring
Temperature ta:	-15...+40 °C

Articles


SNP 1012E LED J/SV

Colors	RAL 9016	RAL (special)
Art. no.	100719241	100719342
recessed ceiling mounting	Light colour: 6500 K	Protection category: IP40




SNP 1012 LED J/SV

Colors	Aluminium	RAL (special)
Art. no.	101238593	101238694
wall or ceiling mounting	Light colour: 6500 K	Protection category: IP40




SNP 1012P LED J/SV

Colors	Aluminium	
Art. no.	100718837	
pendulum mounting	Light colour: 6500 K	Protection category: IP40



SNP 1012S LED J/SV


Colors	Aluminium	RAL (special)
Art. no.	101240011	101240112
cable suspension mounting	Light colour: 6500 K	Protection category: IP40



recessed box for concrete ceiling inst.

Art. no. 100922436

optional



Name	Accessories	Art. no.
Legend panel 1012 10mm - engraved	required	102002570
Legend panel 1012 PL/PR, 10mm	required	101464929
Legend panel 1012 PL/wht, 10mm	required	101464626
Legend panel 1012 PLO/PRO, 10mm	required	101465535
Legend panel 1012 PLO/wht, 10mm	required	101465232
Legend panel 1012 PLU/PRU, 10mm	required	101465636
Legend panel 1012 PLU/wht, 10mm	required	101465434
Legend panel 1012 PO/PO, 10mm	required	101481194
Legend panel 1012 PO/wht, 10mm	required	101465030
Legend panel 1012 PR/wht, 10mm	required	101464727
Legend panel 1012 PRO/wht, 10mm	required	101465131
Legend panel 1012 PRU/wht, 10mm	required	101465333
Legend panel 1012 PU upside-down, 10mm	required	101465737
Legend panel 1012 PU/PU, 10mm	required	101464828
Legend panel 1012 PU/wht, 10mm	required	101464525
Pendulum SN-luminaire 0,5 m gr	required	101440778
Pendulum SN-luminaire 1,0 m gr	required	101440980
Pendulum SN-luminaire 2,0 m gr	required	101441182
conversion kit wire mounting BNP/SNP 1012	optional	101443610
recessed box for concrete ceiling inst.	optional	100922436

Info: When ordering an exit luminaire, the required pictogram with the corresponding arrow direction must be indicated.



Info: For luminaires with pendulum mounting, select the desired pendulum (length and colour of baldachin).